

OASIS 05 SERIES RECESSED ROUND LED DOWNLIGHT

MODEL: OS 605 (T)



Specifications & Technical Data

Luminaires:


- Aluminium Alloy Rim & Housing
- Electrostatically Polyester Powder Coated
- Extruded Aluminium Heatsink
- Aluminium Anodized Reflector
- Polycarbonate Opal Diffuser
- Flex & Nylon Connecting Devices
- Stainless Steel Spring Clips
- Recessed Ceiling Mounted

Areas of Application:

- Home, Hospitality, Hotels, Offices,
- Retail, Supermarkets, Restaurants,
- Public & Commercial Building

Replace:


- 1x26W CFL Downlight &
- Save Over 50% on Energy



Model	System Lumens (lm)	System Power (W)	System Current (A)	Power Factor (λ)	THD	OS LED Modules (DC)	VITALITE LED Driver (AC 220-240V, 50/60Hz)	Hole Cut (mm)
OS 605 (T)	1300lm	15W	0.07A	≥ 0.90	≤ 20%	OS LED 15W/****	VLD 12-18/500 (T)	D150

OS LED Modules (DC)	Total Luminous Flux (lm) With Diffuser	Power (W)	CCT (K)	CRI (Ra)	Max. Temp. Range at ta (°C)	Lifespan (Hrs)
OS LED 15W/3000K	1300lm	15W	3000K	≥ 80	35°C	30000Hrs
OS LED 15W/4000K	1300lm	15W	4000K	≥ 80	35°C	30000Hrs
OS LED 15W/6000K	1300lm	15W	6000K	≥ 80	35°C	30000Hrs

Photometric Data



Flux Out: 371.1 lm

Height (M)	Lux	CM
1	354	115
2	89	231
3	39	346
4	22	462
5	14	577

Height Angle: 60° Diameter