


OASIS D /OL REEDED DIFFUSER SERIES LED BATTEN FITTING c/w INFRARED MOTION SENSOR
MODEL: OS D4-1/OL-IMS
Made to Order

Specifications & Technical Data
Luminaires:

- Housing is Fabricated From Mild Steel (*T 0.5mm*)
- Stove-Coated With High Reflective White Epoxy
- Inner Base is Extruded From Aluminium
- Polycarbonate Reeded Diffuser (*Opal & Linear*)
- Polycarbonate White End Cap
- Nylon Connecting Devices
- Pre-Connected With PVC Cable
- Surface Ceiling / Wall Mounted


Areas of Application:

Home, Hospitality, Hotels, Offices,
Retail, Supermarkets, Restaurants,
Shop Lighting, Storage Room, Staircase
Car Park, Public & Commercial Building

Infrared Motion Sensor:


Hold time **80sec**,
a) Instantly Dim Down **70%** of Power
b) Turn Off Power (**1W±** Power For Standby)
Sensor Distance Range **5Mtr** & Wide **120°**

Optional: VITALITE VECK 36LED **or** VEL 120/ECK
≥ **2** Hours Duration Emergency Powerpack




Model	Diffuser	System Lumens (lm) & Power (W)				LED Strip Module (DC)	VIP LED Driver (AC 220-240V, 50/60Hz, PF 0.90)	Dimension
		Full Load (100%)		Saving Mode (30%)				(mm)
OS D4-1/OL-IMS	Reeded	2400lm	18W	750lm	6W	1 x LED-4FT-STRIP-144-xxxxK-G3 (SMD 2835 12C12B)	1 x VIP 20W/500mA/40V/IMS (Infrared Motion Sensor Driver)	As Shown

LED Strip Module (DC)	Current (mA)	Luminous Flux (lm)	Power (W)	Voltage (V)	CCT (K)			CRI (Ra)	SDCM	Max. Temp. at tc (°C)	Lifespan (Hrs)
LED-4FT-STRIP-144-xxxxK-G3 (SMD 2835 12C12B)	500mA	2880lm	17W	34V	3000K	4000K	6500K	≥ 80	≤ 5	85°C	50000Hrs
	700mA	4000lm	25W	35V	3000K	4000K	6500K	≥ 80	≤ 5	85°C	50000Hrs

Photometric Data


Total Flux (lm): 2415
Imax (cd): 577
Y0008



Total Flux (lm): 787
Imax (cd): 188
Y0008

Date: 02 April 2025

Max. Operating Temperature at ta 0°C to +35°C

YLI INDUSTRY SDN. BHD. Reserves the rights to alternate the specification of its product at any time without prior notice.