


T8 LED Mirror Louver Fitting type RP (Recessed Plaster Ceiling)
Model: OS YML 2222/RP-LED

Specifications & Technical Data

- Housing is Fabricated From Mild Steel (*Thickness 0.5mm*)
- Finished With Powder Electrostatically
- Stove-Coated With High Reflectivity White Epoxy
- Lampholder of Polycarbonate & Bronze
- Twist-Lock Lampholder For Reliable Contact
- Pre-Connected With 105°C HR PVC Cable
- Connecting Devices of Nylon 3 Way x 2.5mm²
- Reflector Louver of Anodized Aluminium, Specular
- Ribbed Cross Blade of Anodized Aluminium in Matt
- Degree of Protection: **IP20**
- Type of Protection: Class 1
- Mounting Method: Recessed Plaster Ceiling

Optional:


VITALITE VECK 18/T8 LED

2 / 3 Hours Duration Emergency Powerpack


Model	Luminaires					Dimension - mm					Current (A)	P.F. (λ)
	No. of Lamp	Power	Beam Angle	Reflector	Base	L1	L2	W1	W2	H	± 5 %	>
OS YML 2222/RP-LED	2	2 x 8W	100°	Anodized	G13	645	614	638	580	82	0.07	> 0.90

Lamp (AC Input 100-240V, 50/60Hz, Athd < 15%) (2ft)

Brand	Code	Type	Base	Lumens (lm)	Power (W)	CCT (K)	CRI (Ra)	SDCM	Current	P.F.	Lifespan (Hrs)
TOSHIBA	T8 LEDtube PRO 600mm 8W 4000K (RLDL0282C0840G1EX1)	T8 LED	G13	1100lm	8W	4000K	≥ 80Ra	≤ 6	0.035	> 0.9	50000Hrs
TOSHIBA	T8 LEDtube PRO 600mm 8W 6500K (RLDL0282C0865G1EX1)	T8 LED	G13	1100lm	8W	6500K	≥ 80Ra	≤ 6	0.035	> 0.9	50000Hrs

Photometric Data


Flux Out: 559.0 lm

(M)	Lux	CM
1	534	115
2	133	231
3	59	346
4	33	462
5	21	577

Height Angle: 60° Diameter