


T8 LED Mirror Louver Fitting type S (Surface Ceiling Mounted / Suspension)
Model: OS YML 4424/S-LED

Specifications & Technical Data

- Housing is Fabricated From Mild Steel (*Thickness 0.5mm*)
- Finished With Powder Electrostatically
- Stove-Coated With High Reflectivity White Epoxy
- Lampholder of Polycarbonate & Bronze
- Twist-Lock Lampholder For Reliable Contact
- Pre-Connected With 105°C HR PVC Cable
- Connecting Devices of Nylon 3 Way x 2.5mm²
- Reflector Louver of Anodized Aluminium, Specular
- Ribbed Cross Blade of Anodized Aluminium in Matt
- Degree of Protection: **IP20**
- Type of Protection: Class 1
- Mounting Method: Surface Ceiling / Suspension

Optional:


VITALITE VECK 18/T8 LED

2 / 3 Hours Duration Emergency Powerpack


Model	Luminaires					Dimension - mm			Current (A)	P.F. (λ)
	No. of Lamp	Power	Beam Angle	Reflector	Base	L	W	H	± 5 %	>
OS YML 4424/S-LED	4	4 x 14W	70°	Anodized	G13	1223	603	80	0.24	> 0.90

Lamp (AC Input 100-240V, 50/60Hz, Athd < 15%) (4ft)

Brand	Code	Type	Base	Lumens (lm)	Power (W)	CCT (K)	CRI (Ra)	SDCM	Current	P.F.	Lifespan (Hrs)
TOSHIBA	T8 LEDtube PRO 1200mm 14W 4000K (RLDL0284C1440G1EX1)	T8 LED	G13	2100lm	14W	4000K	≥ 80Ra	≤ 6	0.06	> 0.9	50000Hrs
TOSHIBA	T8 LEDtube PRO 1200mm 14W 6500K (RLDL0284C1465G1EX1)	T8 LED	G13	2100lm	14W	6500K	≥ 80Ra	≤ 6	0.06	> 0.9	50000Hrs

Photometric Data


Flux Out: 2502 lm

(M)	Lux	CM
1	2389	115
2	597	231
3	265	346
4	149	462
5	96	577

Height Angle: 60° Diameter